


BULLETFCA Flange Coupling Adapter



The BulletFCA by Hawle provides high quality restraint connections to all common water supply pipes. Secures steel, DIP, and PE/PVC pipes with full corrosion protection.

- **DURABLE:** The proven epoxy powder coating provides excellent corrosion protection. Bolts, nuts, washer and locking pistons are made of A4 high grade stainless steel.
- **ADAPTABLE:** With a tolerance of 4° angular deflection at both pipe ends, all types of pipes can easily be connected with BulletFCA.
- **RELIABLE:** BulletFCA by Hawle ensures a restraint connection for all common pipe materials. The clamping elements hold the pipe securely without damage. The elastomer gasket fits snugly around the pipe, creating an effective seal.

Restraint
multi-range
connection
for all
common
pipe types



Flange Size (inches)	Socket Size (inches)	Maximum Operating Pressure (psi)	Adjusting Range FCA Socket (inches)
2	2	145 - 232	2.2 - 2.795
2.5	2.5	145 - 232	2.795 - 3.464
3	2.5	145 - 232	2.795 - 3.464
3	3	145 - 232	3.346 - 4.133
3	4	145 - 232	4.094 - 5.196
4	3	145 - 232	3.346 - 4.133
4	4	145 - 232	4.094 - 5.196
4	5	145 - 232	5.157 - 6.299
5	4	145 - 232	4.094 - 5.196
5	5	145 - 232	5.157 - 6.299
5	6	145 - 232	6.102 - 7.559
6	5	145 - 232	5.157 - 6.299
6	6	145 - 232	6.102 - 7.559
6	8	145 - 232	7.795 - 9.055
8	6	145 - 232	6.102 - 7.559
8	8	145 - 232	7.795 - 9.055
8	9	145 - 232	9.055 - 10.236
10	8	145 - 232	7.795 - 9.055
10	10	145 - 232	10.433 - 12.204
12	12	145 - 232	12.322 - 14.015
14	14	145	13.858 - 15.590
16	16	145	15.669 - 17.401

TECHNICAL SPECIFICATIONS